

Endoscopic optical fibers



- Protection - internal flexible steel braid and an outer sheath of medical silicon
- Crush resistance and bending resistance
- No interference during cooperation with the endoscopic surgical devices
- Surge protection
- full autoclavability
- CE Mark
- Universal sockets made of stainless steel allow the use of adapters for systems of many manufacturers
- HR version available - high temperature resistant, with increased brightness, used with high power light sources
- Fiber Y type allow the connection of two instruments or light sources
- Liquid optical fibers - for optimal transmission of UV radiation

Standard fiber optics		
Catalog No.	Length	Diameter (active)
GF.30.30	3000 mm	3,0 mm
GF.18.35	1800 mm	3,5 mm
GF.23.35	2300 mm	3,5 mm
GF.30.35	3000 mm	3,5 mm
GF.40.35	4000 mm	3,5 mm
GF.18.48	1800 mm	4,8 mm
GF.23.48	2300 mm	4,8 mm
GF.25.48	2500 mm	4,8 mm
GF.30.48	3000 mm	4,8 mm
GF.40.48	4000 mm	4,8 mm

.LE90 – designation in the catalog number – the end of the fiber from the light source angled at 90 °

Manufacturer:

Karlheinz Hinze Optoengineering GmbH&Co.
Kieler Str. 464-470, D - 22525 Hamburg, Germany